# fc37



GH-POWERED 62 HP ENGINE



SWIVEL CAB SEAT

ACCESSORIES & ONFIGURATIONS



#### **SAFE & RUGGED**

Sturdy box-type frame and durable rollers
Thick rubber crawler
Low center of gravity construction for
outstanding durability
Inclination indicator for added safety

### **EASY TO OPERATE**

Class-leading payload of 8,157 lbs.

Dynamic spin-turn capability with independent travel system

Instrument panel concentrated on right side of seat

#### **EASY TO MAINTAIN**

Fully opening engine cover
Ample maintenance around pump
Battery positioned for easy access

## ic37

Townson Company of the Company of th		
IC37 Specifications		
Weight	Transport Weight	6,415 lbs.
	Payload	8,157 lbs.
Ground Pressure	Empty	3.7 psi
	Loaded	8.64 psi
Travel Speed	Low Speed	3.9
	High Speed	6.2
Gradeability Dimensions	Total Length	12'6"
	Total Width	6'2"
	Total Height	7'9"
Engine		
	Model	Kubota V2403-T
	Туре	DI turbo
	Rated Output	62.7 hp @ 2700 rpm
	Fuel Tank Capacity	18 gals
	Battery	12 voH
Crawler		
	Tumbler Center Dist.	8'7"
	Crawler Carier Tot. Width	5'1"
	Crawler Width	13"
	Min. Ground Clearence	1'1"
Vessel		
Capacity	Level	2 yds. <sup>3</sup>
	Heaped	1.5 yds. <sup>3</sup>
Internal Dimensions	Length	7'2"
	Width	4'11"
	Height	1'5"







