

THE SPECS TO SEE YOU THROUGH

Strong on power. Even bigger on performance. Terramac machines are built with the specs you need to get through virtually any job – regardless of what you specialize in.



Straight Frame

MODEL NAME	STRAIGHT FRAME		
	RT6	RT9	RT14
Dimensions	16' 10" L x 8' 2" W x 9' 6" H	19' 6" L x 8' 3" W x 9' 11" H	20' 6" L x 9' 8" W x 10' 5" H
Overall Weight	17,880 lbs with Standard Dump Bed	26,180 lbs with Standard Dump Bed	34,260 lbs with Rock Bed
Ground Pressure - Loaded	5.3 PSI	6.4 PSI	7.4 PSI
Ground Pressure - Unloaded	3.2 PSI	3.8 PSI	4.9 PSI
Maximum Carrying Capacity	12,000 lbs	18,000 lbs	28,000 lbs
Engine	155 HP @ 2200 RPM Cummins B4.5 US T4F / EU Stage V	225 HP @ 2200 RPM Cummins QSB 6.7 T4F	310 HP @ 2200 RPM Cummins QSB 6.7 T4F
Travel Speed - 1st Gear	3.9 mph	2.5 mph	4.0 mph
Travel Speed - 2nd Gear	6.7 mph	5.4 mph	6.8 mph
Gradability	58% (30°)	58% (30°)	58% (30°)
Fuel Capacity	40 gal	64 gal	82 gal



Rotating Frame

MODEL NAME	ROTATING	
	RT7R	RT14R
Dimensions	17' 3" L x 8' 1" W x 9' 9" H	20' L x 9' 8" W x 10' 11" H
Overall Weight	23,730 lbs with Rock Bed	42,200 lbs with Rock Bed
Ground Pressure - Loaded	5.5 PSI	8.3 PSI
Ground Pressure - Unloaded	3.5 PSI	5.0 PSI
Maximum Carrying Capacity	14,000 lbs	28,000 lbs
Engine	165 HP @ 2200 RPM Cummins B4.5 US T4F / EU Stage V	320 HP @ 1800 RPM Cummins QSL9 T4F
Travel Speed - 1st Gear	3.3 mph	3.5 mph
Travel Speed - 2nd Gear	6.7 mph	6.2 mph
Gradability	58% (30°)	58% (30°)
Fuel Capacity	40 gal	90 gal

When historically heavy rains turned jobsites into mud pits, R. H. Price turned to their Terramac RT14R to help install sewage pipe.

“The site conditions have been so wet that we wouldn’t be able to do the job without the RT14R. We need 30-tons of stone for every one hundred feet. If you multiply that many trips over the entire project, it would be nearly impossible to complete with any other machine.”



MODEL NAME	UTILITY		
	RT6U	RT9U	RT14U
Dimensions*	20' 3" L x 8' 2" W x 9' 6" H	24' L x 8' 3" W x 9' 11" H	24' L x 10' W x 10' 5" H
Base Weight	15,020 lbs	20,668 lbs	27,000 lbs
Maximum Carrying Capacity	14,860 lbs	23,512 lbs	35,260 lbs
GVWR	29,880 lbs	44,180 lbs	62,260 lbs
Ground Pressure at Max Weight	5.3 PSI	6.4 PSI	7.4 PSI
Ground Pressure - Unloaded	2.6 PSI	3.0 PSI	3.2 PSI
Engine	155 HP @ 2200 RPM Cummins B4.5 US T4F / EU Stage V	225 HP @ 2200 RPM Cummins QSB 6.7 T4F	310 HP @ 2200 RPM Cummins QSB 6.7 T4F
Travel Speed - 1st Gear	3.9 mph	2.5 mph	4.0 mph
Travel Speed - 2nd Gear	6.7 mph	5.4 mph	6.8 mph
Gradability	58% (30°)	58% (30°)	58% (30°)
Fuel Capacity	40 gal	64 gal	82 gal



Utility Frame

* The overall length may vary depending on utility build model selected.



Jimmy Price
R.H. Price, Inc, President
R.H. PRICE, INC.